

Qty. Description

1 MTR 15-17/7 A-W-A-HUUV



Note! Product picture may differ from actual product

Product No.: [99861290](#)

Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc.

The pump head and base are in cast iron – all other wetted parts are in stainless steel. The pump has the following characteristics:

- Dimensions according to DIN 5440.
- Impellers, intermediate chambers and spline shaft are made of Stainless steel.
- Mechanical shaft seal according to EN 12756.
- Power transmission via sintered metal split coupling.

A cartridge shaft seal ensures high reliability, safe handling, and easy access and service. Immersion depth:

853 mm

Controls:

Frequency converter: NONE

Liquid:

Liquid temperature range: -10 .. 90 °C

Technical:

Pump speed on which pump data are based: 2919 rpm

Rated flow: 17 m³/h

Rated head: 75.7 m

Chambers: 17

Drainage back to tank: N

Pump orientation: Vertical

Code for shaft seal: HUUV

Approvals: CE,EAC

Curve tolerance: ISO9906:2012 3B

Materials:

Pump head: Cast iron
EN 1561 EN-GJL-200
ASTM A48-25B

Impeller: Stainless steel
EN 1.4301
AISI 304

Installation:

Maximum operating pressure: 25 bar

Max pressure at stated temp: 25 bar / 90 °C

Type of connection: G internal thread

Size of outlet connection: 2 inch

Immersion depth: 853 mm

Flange size for motor: FF265

Electrical data:

Motor standard: IEC



Company name:

Created by:

Phone:

Date:

08/05/2023

Qty.	Description
------	-------------

1	Suitable for 50/60 Hz: N
	Others:
	Terminal box position: 6
	Minimum efficiency index, MEI \geq : 0.70
	Net weight: 66.4 kg
	Gross weight: 91.7 kg
	Shipping volume: 0.358 m ³